



| Electrical & Environmental Characteristics | |
|--|------------------------------|
| Impedance | 50 Ohm |
| Operating Frequency | DC~145GHz |
| VSWR | ≤1.60 |
| Operating Temperature | - 55~+125°C |
| | |
| | |
| | |
| Material & Coat-Plating | |
| Inner Conductor | BE-CU, Gold Plated |
| Dielectric | PEI |
| Body | Stainless steel, Passivation |
| | |

| | | | | | |
|---------------------------------------|--|-----------------|--|--------------------|-------------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT | | DWN | Turpanic Co, Ltd ,Inc | | |
| | | CHK | | | |
| Unit mm | TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1° | APVD | Product Model | | |
| | | PRODUCT SPEC | 0.8-KFD013 0.8mm Female with 4FL for PCB Mounting | | |
| | | APPLICATON SPEC | SIZE A4 | GAGE CODE 0T8L4 | DRAWING NO |
| MATEIAL SEE TABLE | FINISH SEE TABLE | WEIGHT | CUSTOMER DRAWING | | SHEET1 OF 1 RVE 1 |
| | | | | | |