

C

C

Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC~110GHz
Dielectric Withstanding Voltage	500V
VSWR	≤1.35
Insertion Loss	≤0.60dB
Operating Temperature	- 55~+125 °C
Material & Coat-Plating	
Inner Conductor	BE-CU, Gold Plated
Dielectric	PEI
Body	Stainless steel, Passivation

B

B

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc	
		CHK		
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		APVD	Product Mode  1.0-KFK 1.0mm Female to 1.0mm Female with 4FL Adaptor
	0 PLC	±0.25	PRODUCT SPEC	
	1 PLC	±0.15		
	2 PLC	±0.12		
3 PLC	±	APPLICATO N SPEC		
3 PLC	±			
ANGLES ±1°				
MATEIAL	FINISH		WEIGHT	SIZE
SEE TABLE	SEE TABLE		A4	0T8L4
			DRAWING NO	
CUSTOMER DRAWING				

A

A



Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC~110GHz
Dielectric Withstanding Voltage	500V
VSWR	≤1.35
Insertion Loss	≤0.60dB
Operating Temperature	- 55~+125 °C
Material & Coat-Plating	
Inner Conductor	BE-CU, Gold Plated
Dielectric	PEI
Body	Stainless steel, Passivation
1	2

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Mode			
		PRODUCT SPEC	1.0-KFK			
		APPLICATION SPEC	1.0mm Female to 1.0mm Female with 4FL Adaptor			
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO	A
		CUSTOMER DRAWING	SCALE 4	SCALE 4: 1	SHEET1 OF 1	RVE 1
3		4		5		