



B	Electrical & Environmental Characteristics	
	Impedance	50 Ohm
C	Insulation Resistance	5000 MΩ
	Operating Frequency	DC~50GHz
—	Dielectric Withstanding Voltage	500 V
	VSWR	≤1.30
—	Insertion Loss	≤0.50dB
	Operating Temperature	- 55~+125℃
A	Material & Coat-Plating	
	Inner Conductor	BE-CU, Gold Plated
	Dielectric	PEI

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc		
		CHK			
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		Product Model 1.0-2.4-JJG 1.0mm Male to 2.4mm Male adaptor		
	0 PLC ±0.25	APVD			
	1 PLC ±0.15	PRODUCT SPEC			
	2 PLC ±0.12				
	3 PLC ±-				
	3 PLC ±-	APPLICATION SPEC			
ANGLES ±1°					
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO



Turpanic Co, Ltd
Email: johnny@turpanic.com
Mob/WeChat/WhatsApp: +8613088887527

—

C

—

B

—

A

—

C

—

B

—

A