



C

C

B

B

Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-40GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.25
Insertion Loss	≤0.05* $\sqrt{f}$ GHz)
Operating Temperature	- 45~+125℃
Material & Coat-Plating	
Inner Conductor	BERYLLIUM COPPER
Dielectric	PEI
STAINLESS STEEL	

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc		
		CHK			
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		Product Model 1.0/2.92-JJ 1.0Male 2.92Male Connector		
	0 PLC	±0.25			PRODUCT SPEC
	1 PLC	±0.15			
	2 PLC	±0.12			
	3 PLC	±			
	3 PLC	±	APPLICATO N SPEC		
	ANGLES ±1°				
		SIZE	GAGE CODE 0T8L4		
		A4			
MATEIAL SEE TABLE		FINISH SEE TABLE	WEIGHT	DRAWING NO	
CUSTOMER DRAWING					
SCALE 4:SCALE 4: 1 SHEET1 OF 1 RVE 1					