



C

C

B

B

Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-40GHz
Dielectric Withstanding Voltag	1000V
VSWR	≤1.25
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 45~+125℃
Material & Coat-Plating	
Inner Conductor	BERYLLIUM COPPER
Dielectric	PEI
STAINLESS STEEL	

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc		
		CHK			
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		Product Model 1.0/2.92-KJ 1.0Female 2.92Male Connector		
	0 PLC	±0.25			PRODUCT SPEC
	1 PLC	±0.15			
	2 PLC	±0.12	APPLICATO N SPEC		
	3 PLC	±			
3 PLC	±				
ANGLES ±1°					
			SIZE	GAGE CODE	DRAWING NO
			A4	0T8L4	
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT			
CUSTOMER DRAWING SCALE 4:SCALE 4: 1 SHEET1 OF 1 RVE 1					