

C											C		
												B	
	<b>Electrical &amp; Environmental Characteristics</b>												
	Impedance	50 Ohm											
	Insulation Resistance	5000 MΩ											
	Operating Frequency	DC~90GHz											
	Dielectric Withstanding Voltage	500V											
	VSWR	≤1.40											
	Insertion Loss	≤0.60dB											
	Operating Temperature	- 55~+125℃											
<b>Material &amp; Coat-Plating</b>										A			
Inner Conductor	BE-CU, Gold Plated												
Dielectric	PEI												
				THIS DRAWING IS A CONTROLLED DOCUMENT		DWN		Turpanic Co, Ltd ,Inc		B			
						CHK							
<b>Unit mm</b>		TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°		APVD		Product Model  1.35/1.0-KJ 1.35mm Female to 1.0mm Male Adaptor				A			
				PRODUCT SPEC									
				APPLICATION SPEC									
MATERIAL SEE TABLE				FINISH SEE TABLE		WEIGHT		SIZE A4		GAGE CODE OT8L4		DRAWING NO	