



Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC~50GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.35
Insertion Loss	≤0.65dB
Operating Temperature	- 55~+125℃
Material & Coat-Plating	
Inner Conductor	BE-CU, Gold Plated
Dielectric	PEI

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc	
		CHK		
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD	Product Model	
	0 PLC ±0.25			
	1 PLC ±0.15	PRODUCT SPEC	2.4-JWKS 2.4mm Male-RA to 2.4mm Female Adaptor	
	2 PLC ±0.12			
	3 PLC ±-			
	3 PLC ±-			
	ANGLES ±1°	APPLICATION SPEC		
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4
			DRAWING NO	



Turpanic Co, Ltd
Email: johnny@turpanic.com
Mob/WeChat/WhatsApp: +8613088887527

—

C

—

B

—

A

—

C

—

B

—

A