



| Electrical & Environmental | |
|---------------------------------|------|
| Impedance | |
| Insulation Resistance | |
| Operating Frequency | |
| Dielectric Withstanding Voltage | |
| VSWR | |
| Insertion Loss | |
| Operating Temperature | |
| Material & Coat-Pl | |
| Inner Conductor | Be |
| Dielectric | |
| Body | Stai |
| Coupling Nut | |

© 2014 TURPANIC

s

5 typ
Hz)

°C

er, Gold

assivated

| | | | | |
|---------------------------------------|---------------------------------------|------------------|---|--------------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT | | DWN | | |
| | | CHK | | |
| Unit mm | TOLERANCES UNLESS OTHERWISE SPECIFIED | APVD | Product Made | ,Inc |
| | 0 PLC ±0.25 | PRODUCT SPEC | 2.4-KYK-02 | |
| | 1 PLC ±0.15 | APPLICATION SPEC | 2.4 Female to 2.4 Female Bulkhead Adaptor | |
| | 2 PLC ±0.12 | | | |
| | 3 PLC ± | | | |
| | 3 PLC ± | | | |
| | ANGLES ±1° | | | |
| MATERIAL SEE TABLE | FINISH SEE TABLE | WEIGHT | SIZE A4 | GAGE CODE OT8L4 |
| | | | | DRAWING NO |
| | | CUSTOMER DRAWING | SCALE 4: 1 | SCALE 4: 1 |
| | | | | SHEET 1 OF 1 |