

C

C

| B Electrical & Environmental Characteristics | |
|--|------------------------|
| Impedance | 50 Ω |
| Insulation Resistance | 5000 MΩ |
| Operating Frequency | DC~40GHz |
| Dielectric Withstanding Voltage | 1000V |
| VSWR | ≤1.15 |
| Insertion Loss | ≤0.05* $\sqrt{f_GHz}$ |
| Operating Temperature | - 55~+165°C |
| Material & Coat-Plating | |
| A Inner Conductor | Beryllium Copper, Gold |
| Dielectric | PEI 1000 |

| No. | Model | Pin Size Ød |
|-----|---------------|--------------|
| 1 | 2.92-JFD80409 | 0.23 [0.009] |
| 2 | 2.92-JFD80412 | 0.30 [0.012] |
| 3 | 2.92-JFD80415 | 0.38 [0.015] |
| 4 | 2.92-JFD80418 | 0.46 [0.018] |
| 5 | 2.92-JFD80420 | 0.51 [0.020] |

| | | | | | |
|---------------------------------------|---------------------------------------|------------------|---|-----------------|------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT | | DWN | Turpanic Co, Ltd ,Inc | | |
| | | CHK | | | |
| Unit mm | TOLERANCES UNLESS OTHERWISE SPECIFIED | APVD | Product Model | | |
| | 0 PLC ±0.25 | | 2.92-JFD80418 2.92mm male Flange Connector | | |
| | 1 PLC ±0.15 | PRODUCT SPEC | | | |
| | 2 PLC ±0.12 | | | | |
| | 3 PLC ± | | | | |
| | 3 PLC ± | | | | |
| | ANGLES ±1° | APPLICATION SPEC | | | |
| MATERIAL SEE TABLE | FINISH SEE TABLE | WEIGHT | SIZE A4 | GAGE CODE OT8L4 | DRAWING NO |