Turpanic

C   C

1.6

12.9

Ø14

10.2

4.8

B   B

Electrical & Environmental Characteristics

Impedance	50 Ohm
Insulation Resistance	3000 MΩ
Operating Frequency	40GHz
Dielectric Withstanding Voltage	750 V
VSWR	1.15
Insertion Loss	$0.05*Sqt(f\_GHz)$
Operating Temperature	-55~+165℃

Material & Coat-Plating

Inner Conductor	Beryllium Copper, Gold
Dielectric	PEI
Body	Stainless Steel, Passivated
Coupling Nut	N/A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc		
		CHK			
Unit **mm**	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ±- 3 PLC ±- ANGLES ±1°	APVD	**Product Mode** **2.92-JFD80512** **2.92 Male Flange Connector**		
		PRODUCT SPEC			
		APPLICATON SPEC			
			SIZE A4	GAGE CODE 0T8L4	DRAWING NO
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT			
		CUSTOMER DRAWING	SCALE 4:SCALE 4: 1	SHEET1 OF 1	RVE 1

A   A