

C

C

|                                                       |                        |
|-------------------------------------------------------|------------------------|
| <b>Electrical &amp; Environmental Characteristics</b> |                        |
| Impedance                                             | 50 Ω                   |
| Insulation Resistance                                 | 5000 MΩ                |
| Operating Frequency                                   | DC~40GHz               |
| Dielectric Withstanding Voltage                       | 1000V                  |
| VSWR                                                  | ≤1.15                  |
| Insertion Loss                                        | ≤0.05* $\sqrt{f\_GHz}$ |
| Operating Temperature                                 | - 55~+165℃             |
| <b>Material &amp; Coat-Plating</b>                    |                        |
| Inner Conductor                                       | Beryllium Copper, Gold |
| Dielectric                                            | PEI 1000               |

A

| No. | Model         | Pin Size Ød  |
|-----|---------------|--------------|
| 1   | 2.92-JFD80709 | 0.23 [0.009] |
| 2   | 2.92-JFD80712 | 0.30 [0.012] |
| 3   | 2.92-JFD80715 | 0.38 [0.015] |
| 4   | 2.92-JFD80718 | 0.46 [0.018] |
| 5   | 2.92-JFD80720 | 0.51 [0.020] |

B

|                                       |                                                                                                                          |                                                  |                                                                                  |                    |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------------------------------|--------------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT |                                                                                                                          | DWN                                              | Turpanic Co, Ltd ,Inc                                                            |                    |
|                                       |                                                                                                                          | CHK                                              |                                                                                  |                    |
| Unit<br>mm                            | TOLERANCES UNLESS OTHERWISE SPECIFIED<br>0 PLC ±0.25<br>1 PLC ±0.15<br>2 PLC ±0.12<br>3 PLC ±-<br>3 PLC ±-<br>ANGLES ±1° | APVD<br><br>PRODUCT SPEC<br><br>APPLICATION SPEC | Product Model<br><br><b>2.92-JFD80712</b><br><b>2.92mm male Flange Connector</b> |                    |
| MATERIAL<br>SEE TABLE                 | FINISH<br>SEE TABLE                                                                                                      | WEIGHT                                           | SIZE<br>A4                                                                       | GAGE CODE<br>0T8L4 |
|                                       |                                                                                                                          |                                                  | DRAWING NO                                                                       |                    |

A