


C



C

B

## Electrical & Environmental Characteristics

Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-40GHz
Dielectric Withstanding Voltage	500V
VSWR	≤1.25
Insertion Loss	≤0.4dB
Operating Temperature	- 55~+125℃

B

扫描类型	起始频率 (GHz)	终止频率 (GHz)	扫描点数	中频带宽 (Hz)	扫描时间 (s)	端口1,2功率 (dBm)
通道1 线性扫描	0.010000000	40.000000000	801	1000	0.779105	-5.00,-5.00

A

Inner Conductor	Beryllium copper gilding
Dielectric	PEI

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN CHK	Turpanic Co, Ltd ,Inc	
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		Product Model	
	0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	PRODUCT SPEC	2.92-KFK 2.92 Female 2.92 Female Connector	
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE OT8L4
CUSTOMER DRAWING			SCALE 4: 1	DRAWING NO
			SCALE 4: 1	SHEET1 OF 1
				RVE 1