



Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC~33GHz
Dielectric Withstanding Voltage	1000 V
VSWR	≤1.25
Insertion Loss	≤0.35dB
Operating Temperature	- 55~+125℃
Material & Coat-Plating	
Inner Conductor	BE-CU, Gold Plated
Dielectric	PEI

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc	
		CHK		
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		Product Model	
	0 PLC	±0.25	3.5-2.4-KKG 3.5mm Female to 2.4mm Female adaptor	
	1 PLC	±0.15		
	2 PLC	±0.12		
	3 PLC	±-		
	3 PLC	±-		
		ANGLES ±1°		
		PRODUCT SPEC		
		APPLICATION SPEC		
MATERIAL SEE TABLE		FINISH SEE TABLE	WEIGHT	
			SIZE A4	GAGE CODE 0T8L4
				DRAWING NO



Turpanic Co, Ltd
Email: johnny@turpanic.com
Mob/WeChat/WhatsApp: +8613088887527

—

C

—

B

—

A

—

C

—

B

—

A