

0.86mm NbTi/CuNi cryogenic Cable Assemblies

G034NTCN /SMA Male / SMA Male/DC-18 GHz

Model: G034NTCN-SMAMSMAM-L



Features:

- Max Frequency 18 GHz
- VSWR max of 1.35


Applications:

- Dilution refrigerators/Cryogenic devices
- Quantum Computing
- Vacuum Chambers

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	DC		18	GHz
VSWR		1.25	1.35	:1
Shielding Effectiveness	110			dB
Capacitance			95.2	pF/m
Impedance		50		ohm

Cable Cross Section:




Environmental And Physical Characteristics:

Description	Parameter	Units
Cable Diameter	0.86	mm
Min. Bending Radius	3.2	mm
Thermal conductivity@4-20K	31	$\mu\text{w/k}$
Operating Temperature	10mK To +200	$^{\circ}\text{C}$
Storage Temperature	-55 to +200	$^{\circ}\text{C}$

Connectors:

Description	Connector 1	Connector 2
Type	SMA Straight Male	SMA Straight Male
Contact Material And Plating	Brass,Gold	Brass,Gold
Dielectric Type	PTFE	PTFE
Body Material And Plating	Oxygen-free copper	Oxygen-free copper
Insertion Loss (dB Max)	$0.05 * \sqrt{f_GHz}$	$0.05 * \sqrt{f_GHz}$

Outline Drawing:



Ordering Information:

Base Number	Length (Unit mm)	Custom Design Services
G034NTCN-SMAMSMAM	-L	LEAVE BLANK(NOT REQUIRED) -CB(Precision CNC Bends)