



Electrical & Environmental Characteristics

| | |
|---------------------------------|------------------------|
| Impedance | 50 Ohm |
| Insulation Resistance | 5000 MΩ |
| Operating Frequency | 18 GHz |
| Dielectric Withstanding Voltage | 1500 V |
| VSWR | 1.15 |
| Insertion Loss | 0.05* $\sqrt{f_{GHz}}$ |
| Operating Temperature | -55~+165°C |

Material & Coat-Plating

| | |
|-----------------|-----------------------------|
| Inner Conductor | Beryllium Copper, Gold |
| Dielectric | PEI&PTFE |
| Body | Stainless Steel, Passivated |
| Coupling Nut | Stainless Steel, Passivated |

| | | | | | |
|---------------------------------------|--|------------------|---------------------------------------|--------------------|------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT | | DWN | Turpanic Co, Ltd ,Inc | | |
| | | CHK | | | |
| Unit mm | TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1° | APVD | Product Mode | | |
| | | PRODUCT SPEC | N-JFD80920 N Male Flange Connector | | |
| | | APPLICATION SPEC | | | |
| MATERIAL SEE TABLE | FINISH SEE TABLE | WEIGHT | SIZE A4 | GAGE CODE 0T8L4 | DRAWING NO |
| | | CUSTOMER DRAWING | SCALE 4: SCALE 4: 1 | SHEET1 OF 1 | RVE 1 |