



| B Electrical & Environmental Characteristics | |
|---|--------------------|
| Impedance | 50 Ohm |
| Insulation Resistance | 5000 MΩ |
| Operating Frequency | DC~18GHz |
| Dielectric Withstanding Voltage | 1500V |
| VSWR | 1.35Max |
| Insertion Loss | ≤0.30dB |
| Operating Temperature | - 55~+125°C |
| Material & Coat-Plating | |
| A Inner Conductor | BE-CU, Gold Plated |
| Dielectric | PTFE |

| | | | | |
|---------------------------------------|---------------------------------------|------------------|-------------------------------|-----------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT | | DWN CHK | Turpanic Co, Ltd ,Inc | |
| Unit mm | TOLERANCES UNLESS OTHERWISE SPECIFIED | | Product Model | |
| | 0 PLC ±0.25 | APVD | N-JWK | |
| | 1 PLC ±0.15 | PRODUCT SPEC | N Male-RA to N Female adaptor | |
| | 2 PLC ±0.12 | | | |
| | 3 PLC ± | | | |
| | 3 PLC ± | APPLICATION SPEC | | |
| | ANGLES ±1° | | | |
| MATERIAL SEE TABLE | FINISH SEE TABLE | WEIGHT | SIZE A4 | GAGE CODE OT8L4 |
| | | | | DRAWING NO |