

C

C

B	Electrical & Environmental Characteristics	
	Impedance	50 Ω
	Insulation Resistance	5000 MΩ
	Operating Frequency	DC~18GHz
	Dielectric Withstanding Voltage	2500V
	VSWR	≤1.15
	Insertion Loss	≤0.05* $\sqrt{f_{GHz}}$
	Operating Temperature	- 55~+165 °C
A	Material & Coat-Plating	
	Inner Conductor	Beryllium Copper, Gold
	Dielectric	PTFE
	Body	Stainless Steel,Passivated

No.	Model	D1(Diameter1)	D2(Diameter2)	L1(Length1)	L2(Length2)	T(Thickness)	B	
1	N-KFD010713	4.1 [0.161]	1.27 [0.05]	4 [0.157]	1.5 [0.059]	0.2 [0.008]		
THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc					
		CHK						
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD	Product Model N-KFD010713 N Female Flange Connector					
	0 PLC ±0.25	PRODUCT SPEC						
	1 PLC ±0.15							
	2 PLC ±0.12							
	3 PLC ±-	APPLICATON SPEC	SIZE A4					
	3 PLC ±-							
	ANGLES ±1°							
	MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	GAGE CODE OT8L4				DRAWING NO
CUSTOMER DRAWING			SHEET1 OF 1					RVE 1