



Electrical & Environmental Characteristics

Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	18 GHz
Dielectric Withstanding Voltage	2000 V
VSWR	1.15typ
Insertion Loss	0.05* $\sqrt{f_GHz}$
Operating Temperature	-55~+165°C

Material & Coat-Plating

Inner Conductor	Beryllium Copper, Gold
Dielectric	PEI
Body	Stainless Steel, Passivated

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN CHK	Turpanic Co, Ltd ,Inc	
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD	Product Mode N-KKS N Female to N Female Adaptor	
	0 PLC ±0.25	PRODUCT SPEC		
	1 PLC ±0.15			
2 PLC ±0.12				
	3 PLC ±	APPLICATO N SPEC		
	3 PLC ±		SIZE A4	GAGE CODE 0T8L4
	ANGLES ±1°			DRAWING NO
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	CUSTOMER DRAWING	

SCALE 4 SCALE 4: 1 SHEET1 OF 1 RVE 1