

C

C

B

B

| Electrical & Environmental Characteristics | |
|--|--------------------------|
| Impedance | 50 Ohm |
| Insulation Resistance | 5000MΩ |
| Operating Frequency | DC-40GHz |
| Dielectric Withstanding Voltage | 1000V |
| VSWR | ≤1.20 |
| Insertion Loss | 0.05* $\sqrt{f_GHz}$ |
| Operating Temperature | - 55~+165℃ |
| Inner Conductor | Beryllium copper gilding |
| Dielectric | PEI |

A

A

| | | | | |
|---------------------------------------|---------------------------------------|------------------|-------------------------------------|--------------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT | | DWN CHK | Turpanic Co, Ltd ,Inc | |
| Unit mm | TOLERANCES UNLESS OTHERWISE SPECIFIED | | Product Model | |
| | 0 PLC ±0.25 | 1 PLC ±0.15 | NMD2.4F2.92F | |
| | 2 PLC ±0.12 | PRODUCT SPEC | NMD2.4 Female 2.92 Female Connector | |
| | 3 PLC ± | APPLICATION SPEC | | |
| | 3 PLC ± | | | |
| | ANGLES ±1° | | SIZE A4 | GAGE CODE OT8L4 |
| MATERIAL SEE TABLE | FINISH SEE TABLE | WEIGHT | DRAWING NO | |
| CUSTOMER DRAWING | | | SCALE 4: 1 | SCALE 4: 1 |
| | | | SHEET 1 OF 1 | RVE 1 |