

C

C

B

B



Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-50GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.25
Insertion Loss	≤0.06* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165℃

Material & Coat-Plating	
Inner Conductor	Beryllium bronze passivation
Dielectric	PEI

Stainless steel SUS303 passivated

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN CHK	Turpanic Co, Ltd ,Inc	
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD PRODUCT SPEC APPLICATION SPEC	Product Model	
			NMD2.4FNMD2.4F NMD2.4 Female NMD2.4 Female Connector	
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE OT8L4
				DRAWING NO
				CUSTOMER DRAWING
				SCALE 4: 1 SCALE 4: 1 SHEET1 OF 1 RVE 1