



Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-50GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.25
Insertion Loss	0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165℃
Material & Coat-Plating	
Inner Conductor	Beryllium bronze gilding
Dielectric	PEI

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN CHK	Turpanic Co, Ltd ,Inc	
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		Product Model	
	0 PLC ±0.25	1 PLC ±0.15	NMD2.4FNMD2.4M	
	2 PLC ±0.12	PRODUCT SPEC	NMD2.4 Female NMD2.4 Male	
	3 PLC ±	APPLICATION SPEC	Connector	
	3 PLC ±			
	ANGLES ±1°			
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE OT8L4
CUSTOMER DRAWING			DRAWING NO	
		SCALE 4: 1	SCALE 4: 1	SHEET 1 OF 1
				RVE 1