

C

C

B

B



Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-40GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.2
Insertion Loss	≤0.06* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165℃
Material & Coat-Plating	
Inner Conductor	Beryllium bronze passivation
Dielectric	PEI
Stainless steel SUS303 passivated	

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc				
		CHK					
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model NMD2.92F2.4F NMD2.92 Female 2.4 Female Connector				
		PRODUCT SPEC					
		APPLICATION SPEC					
MATEIAL SEE TABLE		FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE OT8L4	DRAWING NO	
			CUSTOMER DRAWING		SCALE 4: 1 SCALE 4: 1	SHEET1 OF 1	RVE 1