

## PLDRO-25000-13-INT

25 GHz PLDRO , 13 dBm, Internal reference

### 电气参数 Electrical Characteristics:


参数Parameter	Min	Typ	Max	指标 Value
输出频率 Output Frequency		25		GHz
输出功率 Output Power	13	14.5		dBm
参考信号 Reference	Internal			
频率稳定度 Frequency stability			±0.1	ppm
相位噪声 Phase noise		-83	-78	dBc/Hz@100Hz
		-107	-102	dBc/Hz@1KHz
		-116	-110	dBc/Hz@10KHz
		-115	-110	dBc/Hz@100KHz
		-139	-130	dBc/Hz@1MHz
杂散抑制 Spurious		-72	-70	dBc
1/2 杂散 Spurious		-61	-60	dBc
谐波抑制 Harmonics			-20	dBc
电源电压 DC Voltage		12		V
工作电流 DC Current		360	600	mA
锁相指示 Phase-lock indicator	TTL High			

### 环境和物理特性 Environmental And Physical Characteristics:

参数Parameter	指标 Value
操作温度 Operating Temperature	-40°C to +70°C
存储温度 Storage temperature	-45°C to +75°C
震动 Vibration(operating)	10G RMS, 20-2000HZ
冲击 Shock(non operating)	50G, 1/2Sine, 12msec
射频接口 Connector Type	SMA Female
直接接口 DC Connector	PIN


## 外形尺寸 Outline Drawing:

Unit: mm



## 典型相位噪声曲线 Typical Phase noise Performance Data:

Phase Noise



## 订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号 Revision
------------------	----------------	--------------