

SPDT Coaxial Switches

R12-KF12040-01 , Coaxial Switches , SPDT , 2.92mm , Failsafe , 12VDC , DC to 40 GHz , 2 Pin(2.54mm)

R12-KF24040-01 , Coaxial Switches , SPDT , 2.92mm , Failsafe , 24VDC , DC to 40 GHz , 2 Pin(2.54mm)

R12-KF28040-01 , Coaxial Switches , SPDT , 2.92mm , Failsafe , 28VDC , DC to 40 GHz , 2 Pin(2.54mm)

电气参数 Electrical Characteristics:

参数Parameter	条件Condition
频率范围 Frequency range	DC-40GHz
阻抗 Impedance	50 Ω
开关模式 Operation mode	Failsafe
开关顺序 Switch sequence	Break before make
切换时间 Switching time	15 ms max
机械寿命 Mechanical life	5 million min
TTL input	0-0.8 V(OFF), 2.4-5 V(ON)
额定电压 Rated voltage	12 24 28 VDC
工作电流 Operating current at 23 °C	190 98 83 mA




射频特性 RF Specifications:

频率范围 FREQUENCY RANGE(GHz)	DC-6	6-12	12-18	18-26.5	26.5-40
插入损耗 INSERTION LOSS (MAX) dB	0.2	0.25	0.4	0.7	1.0
隔离度 ISOLATION (MIN) dB	70	70	60	55	50
电压驻波比 V.S.W.R. (MAX)	1.2:1	1.3:1	1.4:1	1.7:1	2.0:1


环境和物理特性 Environmental And Physical Characteristics:

参数 Parameter	条件 Condition
工作温度范围 Operating temperature range	-25°C to +65°C(Standard) -55°C to +85°C(Optional)
振动 Sine vibration(Operating)	20-2000Hz , 10g
冲击 Shocks(Non Operating)	50g / 12ms, ½ine


外形尺寸 Outline Drawing: Unit: mm



原理图 Schematic:



功率曲线图 Average power:



This graph is based on the following conditions:

- Ambient temperature: + 25 °C
- Sea level
- V.S.W.R.: 1 and cold switching

标准型号 Part Number:

标准型号 Part Number

SPDT

R12-KF12040-01

额定电压
Rated Voltage


12VDC

可选项 Option


-S

典型曲线 Typical Performance Data:

INSERTION LOSS



VSWR



ISOLATION

