

DPDT Coaxial Switches

R22-SF12T18-D, Coaxial Switches, DPDT, SMA, Failsafe, 12VDC, TTL, DC to 18 GHz, DSUB-9

R22-SF24T18-D, Coaxial Switches, DPDT, SMA, Failsafe, 24VDC, TTL, DC to 18 GHz, DSUB-9

R22-SF28T18-D, Coaxial Switches, DPDT, SMA, Failsafe, 28VDC, TTL, DC to 18 GHz, DSUB-9

电气参数 Electrical Characteristics:

参数Parameter	条件Condition
频率范围 Frequency range	DC-18GHz
阻抗 Impedance	50 Ω
开关模式 Operation mode	Failsafe
开关顺序 Switch sequence	Break before make
切换时间 Switching time	15 ms max
机械寿命 Mechanical life	2 million min
TTL input	0-0.8 V(OFF), 2.4-5 V(ON)
额定电压 Rated voltage	12 24 28 VDC
工作电流 Operating current at 23 °C	380 200 180 mA




射频特性 RF Specifications:

频率范围 FREQUENCY RANGE(GHz)	DC-6	6-12	12-18
插入损耗INSERTION LOSS (MAX) dB	0.2	0.25	0.4
隔离度 ISOLATION (MIN) dB	70	70	60
电压驻波比 V.S.W.R. (MAX)	1.3:1	1.4:1	1.5:1


环境和物理特性 Environmental And Physical Characteristics:

参数Parameter	条件 Condition
工作温度范围 Operating temperature range	-25°C to +65°C(Standard) -55°C to +85°C(Optional)
振动 Sine vibration(Operating)	20-2000Hz , 10g
冲击 Shocks(Non Operating)	50g / 11ms, ½ sine
射频接口 RF Connector type	SMA Female

外形尺寸 Outline Drawing: Unit: mm



原理图 Schematic:




功率曲线图 Average power:

This graph is based on the following conditions:

- Ambient temperature: + 25 °C
- Sea level

针脚定义 Pin Definition:



9 PIN D-SUB		RF Connect Used
Pin NO.	Function	DPDT
1	A1(TTL IN)	NO:J1-J2,J3-J4
	0	NC:J1-J3,J2-J4
2	UNUSED	
3	COM-	
4-9	UNUSED	

标准型号 Part Number:

标准型号 Part Number

驱动电压

可选项 Option

DPDT

Actuator voltage


R22-SF12T18-D

12VDC


-S

典型曲线 Typical Performance Data:

VSWR



INSERTION LOSS



ISOLATION

