

Part No: RAXXA2-N-8

N Attenuators • Male to Female • DC – 12.4 GHz -2W

电气特性 ELECTRICAL

- **Frequency Range** DC – 12.4 GHz
- **Attenuation (dB)**
 - 1 through 9 ± 0.7 dB
 - 10 ± 0.7 dB
 - 20 ± 0.7 dB
 - 30 ± 0.7 dB
 - 40 ± 0.75 dB
 - 50 ± 0.75 dB
- **VSWR (MAX)**
 - DC – 4 GHz..... 1.20 : 1
 - 4 - 8 GHz1.30 : 1
 - 8 - 12.4 GHz.....1.35 : 1
- **Impedance** 50 Ohms
- **RF Power Nominal** 2 Watts Average at 25°C
PEAK: 500 Watts
(5 μ Sec Pulse Width , 0.4% Duty Cycle)

机械特性 MECHANICAL

- **Temperature Range** -55°C - +125°C
- **Connectors** Brass , Nickel Plated
- **Connector Pins** Beryllium Copper, Gold Plated
- **Body** Aluminum
- **Insulators** PTFE, Virgin Electrical Grade

订货信息 ORDER

Model Number : RAXXA2-N-12.4



Connector: N and TNC are optional.
Unit : mm