

C

C

B

B

Electrical & Environmental Characteristics	
Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~26.5GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165℃
Material & Coat-Plating	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PTFE
Body	Stainless Steel, Passivated

A

A

No.	Model	D(Diameter)	L(Length)	T(Thickness)
1	SMA-KFD40114	1.27 [0.050]	1.27 [0.050]	0.15 [0.006]
2	SMA-KFD40114-098	1.27 [0.025]	2.50 [0.098]	0.13 [0.005]
3				
4				
THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc	
		CHK		
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ±- 3 PLC ±- ANGLES ±1°	APVD	Product Model SMA-KFD40114 SMA Female Flange Connector	
		PRODUCT SPEC		
		APPLICATION SPEC		
		SIZE A4	GAGE CODE 0T8L4	DRAWING NO
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT		
		CUSTOMER DRAWING		SHEET1 OF 1 RVE 1