

C

C

B

B

Electrical & Environmental Characteristics	
Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~26.5GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165℃
Material & Coat-Plating	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PTFE
Body	Stainless Steel, Passivated

A

A

		No.	Model	D(Diameter)	L(Length)	T(Thickness)
		1	SMA-KFD405C11	0.64 [0.025]	4 [0.157]	0.2 [0.008]
		2	SMA-KFD405C11-04	0.64 [0.025]	1 [0.039]	0.2 [0.008]
		3	SMA-KFD405C11-787	0.64 [0.025]	2 [0.079]	0.2 [0.008]
		4	SMA-KFD405C11-2M	0.64 [0.025]	6 [0.236]	0.2 [0.008]

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd, Inc			
		CHK				

Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ±- 3 PLC ±- ANGLES ±1°	APVD	Product Model SMA-KFD405C11 SMA Female Flange Connector				
		PRODUCT SPEC					
APPLICATON SPEC							
SIZE A4		GAGE CODE 0T8L4					DRAWING NO
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT					
		CUSTOMER DRAWING				SHEET1 OF 1	RVE 1