

C

B

Electrical & Environmental Characteristics	
Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~26.5GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165℃
Material & Coat-Plating	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PTFE

A

No.	Model	D(Diameter)	L(Length)
1	SMA-KFD50612-078	0.30 [0.012]	2 [0.079]
2	SMA-KFD50620-236	0.50 [0.020]	6 [0.236]
3	SMA-KFD50624-1024	0.60 [0.024]	26 [1.024]
4	SMA-KFD50625-98	0.64 [0.025]	2.5 [0.098]
5	SMA-KFD50625-236	0.64 [0.025]	6 [0.236]
6	SMA-KFD50625-787	0.64 [0.025]	20.8 [0.819]
7	SMA-KFD50625-709	0.64 [0.025]	18 [0.709]
8	SMA-KFD50631-839	0.80 [0.031]	21.3 [0.839]
9	SMA-KFD50631-980	0.80 [0.031]	24.9 [0.980]
10	SMA-KFD50631-2362	0.80 [0.031]	60 [2.362]
11	SMA-KFD50634-430	0.87 [0.034]	10.92 [0.430]
12	SMA-KFD50634-818	0.87 [0.034]	20.8 [0.819]
13	SMA-KFD50634-1024	0.87 [0.034]	26 [1.024]
14	SMA-KFD50634-1388	0.87 [0.034]	35 [1.378]

C

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc		
		CHK			
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD	Product Model SMA-KFD50625-787 SMA Female Flange Connector		
	0 PLC ±0.25	PRODUCT SPEC			
	1 PLC ±0.15				
	2 PLC ±0.12				
	3 PLC ±-				
3 PLC ±-	APPLICATION SPEC				
ANGLES ±1°					
MATERIAL	FINISH	WEIGHT	SIZE	GAGE CODE	DRAWING NO
SEE TABLE	SEE TABLE		A4	0T8L4	
CUSTOMER DRAWING					

A