



B	Electrical & Environmental Characteristics	
	Impedance	50 Ω
	Insulation Resistance	5000 MΩ
	Operating Frequency	DC~26.5GHz
	Dielectric Withstanding Voltage	1000V
	VSWR	≤1.15
	Insertion Loss	≤0.05* $\sqrt{f_GHz}$
	Operating Temperature	- 55~+165℃
	Material & Coat-Plating	
A	Inner Conductor	Beryllium Copper, Gold
	Dielectric	PTFE

		No.	Model	D(Distance)	L(Length)	T(Thickness)	B	
		1						
THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd, Inc					
		CHK						
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD	Product Model SMA-KHD01L1 SMA Female Connector					
	0 PLC ±0.25	PRODUCT SPEC						
	1 PLC ±0.15							
	2 PLC ±0.12							
	3 PLC ±-							
	3 PLC ±-							
	ANGLES ±1°	APPLICATO N SPEC						
MATEIAL	FINISH	WEIGHT	SIZE	GAGE CODE	DRAWING NO			A
SEE TABLE	SEE TABLE		A4	0T8L4				
CUSTOMER DRAWING								