



<b>Electrical &amp; Environmental Characteristics</b>	
Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~26.5GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f\_GHz}$
Operating Temperature	- 55~+165°C
<b>Material &amp; Coat-Plating</b>	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PTFE

No.	Model	D(Distance)	L(Length)	T(Thickness)
1				

  

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc		
		CHK			
<b>Unit</b>	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD	<b>Product Model</b>  <b>SMA-KHD02L1</b> <b>SMA Female Connector</b>		
<b>mm</b>	0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ±- ANGLES ±1°	PRODUCT SPEC			
MATEIAL	FINISH	WEIGHT	SIZE	GAGE CODE	DRAWING NO
SEE TABLE	SEE TABLE		A4	OT8L4	

CUSTOMER DRAWING