

C

C

Electrical & Environmental Characteristics	
Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~26.5GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165℃
Material & Coat-Plating	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PTFE

A

		No.	Model	D(Distance)	L(Length)	T(Thickness)	B
		1					
THIS DRAWING IS A CONTROLLED DOCUMENT			DWN	Turpanic Co, Ltd ,Inc			
			CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD	Product Model SMA-KHD03L1 SMA Female Connector				
	0 PLC ±0.25	PRODUCT SPEC					
	1 PLC ±0.15						
	2 PLC ±0.12						
	3 PLC ±-	APPLICATO N SPEC					
	3 PLC ±-						
	ANGLES ±1°						
MATEIAL	FINISH	WEIGHT	SIZE	GAGE CODE	DRAWING NO		A
SEE TABLE	SEE TABLE		A4	0T8L4			
CUSTOMER DRAWING							

A