

C

C

Electrical & Environmental Characteristics	
Impedance	50 Ω
Insulation Resistance	5000 M Ω
Operating Frequency	DC~26.5GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤ 1.15
Insertion Loss	$\leq 0.05 * \text{Sq}(f_GHz)$
Operating Temperature	- 55~+165 $^{\circ}\text{C}$
Material & Coat-Plating	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PTFE

A

		No.	Model	D(Distance)	L(Length)	T(Thickness)	B	
		1						
THIS DRAWING IS A CONTROLLED DOCUMENT			DWN	Turpanic Co, Ltd ,Inc				
			CHK					
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD	Product Model SMA-KHD05L1 SMA Female Connector					
	0 PLC ±0.25	PRODUCT SPEC						
	1 PLC ±0.15							
	2 PLC ±0.12							
	3 PLC ±-	APPLICATO N SPEC						
	3 PLC ±- ANGLES ±1°							
MATEIAL SEE TABLE		WEIGHT	SIZE A4	GAGE CODE OT8L4			DRAWING NO	A
FINISH SEE TABLE		CUSTOMER DRAWING						

A