

C

C

B

B

<b>Electrical &amp; Environmental Characteristics</b>	
Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~26.5GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.2
Insertion Loss	≤0.05* $\sqrt{f\_GHz}$
Operating Temperature	- 55~+165°C
<b>Material &amp; Coat-Plating</b>	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PTFE

A

A

No.	Model	Pin Size Ød

  

THIS DRAWING IS A CONTROLLED DOCUMENT	DWN	Turpanic Co, Ltd ,Inc
	CHK	
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	Product Model  <b>SMA-KWFD1330-F12</b> <b>SMA Female Right Angle Square-Flange for PCB</b>
	0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	
MATEIAL SEE TABLE	FINISH SEE TABLE	APPLICATO N SPEC
WEIGHT	SIZE A4	GAGE CODE 0T8L4
		DRAWING NO