



1 | 3 | 4 | 5

D

C

B

A

**Electrical & Environmental**

- Impedance
- Insulation Resistance
- Operating Frequency
- Dielectric Withstanding Voltage
- VSWR
- Insertion Loss
- Operating Temperature

1.2

**Material & Coat-Pl**

- Inner Conductor
- Dielectric
- Body
- Coupling Nut

Be

Stai

© 2014 TURPANIC

s

@18GHz  
Hz)  
°C

er, Gold  
assivated

THIS DRAWING IS A CONTROLLED DOCUMENT

Unit  
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED  
0 PLC ±0.25  
1 PLC ±0.15  
2 PLC ±0.12  
3 PLC ±  
3 PLC ±  
ANGLES ±1°

MATERIAL  
SEE TABLE

FINISH  
SEE TABLE

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

SIZE  
A4

GAGE CODE  
OT8L4

DRAWING NO

SHEET 1 OF 1

Product Made

SMA Female to SMA Female Right Angl  
Adaptor

Turpannic Co., Inc

,Inc

**SMA-KWKS**

SCALE 4: 1 SCALE 4: 1

5

3

4

1