

**Part No: TAXXA2-S-18**

**SMA Attenuators • Male to Female • DC - 18 GHz-2W**

**电气特性 ELECTRICAL**

- **Frequency Range** DC - 18 GHz
- **Attenuation (dB)** 1 through  $9 \pm 0.30$  dB  
 $10, 20 \pm 0.50$  dB  
 $25, 30 \pm 0.75$  dB
- **VSWR (MAX)** DC - 4 GHz.....1.15:1  
 4 - 8 GHz.....1.20:1  
 8 - 12.4 GHz.....1.25:1  
 12.4 - 18 GHz...1.35:1
- **Impedance** 50 Ohms
- **RF Power Nominal** 2 Watt Average at 25°C  
 (5  $\mu$ Sec Pulse, 0.05% Duty Cycle)  
 PEAK: 250 WATTS



**机械特性 MECHANICAL**

- **Temperature Range** -65°C - +125°C
- **Connectors** Passivated Stainless Steel
- **Connector Pins** Beryllium Copper, Gold Plated
- **Housing** Passivated Stainless Steel
- **Insulators** PTFE, Virgin Electrical Grade

**订货信息 ORDER**

**Model Number:** TAXXA2-S-18  
 └──────────┬──────────  
                   dB Value

