

## Coaxial Fixed Attenuator

N Female&Male/DC-12.4GHz

Model:TAXXA25-N-12.4

TAXXA25-N-12.4 is a 3/6/10/20/30/40 dB coaxial attenuator that is used in millimeterwave systems and operates from DC to 12.4 GHz.

### Features:

- Operating Frequency DC to 12.4GHz
- Broadband Coverage
- Lost Cost

### Applications:

- Test Lab
- Instrumentations
- System Integration



### 电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency Range	DC		12.4	GHz
衰减范围 Attenuation Range		3±0.8		dB
		6±0.8		dB
		10±0.8		dB
		20±0.8		dB
		30±1.0		dB
		40±1.0		dB
驻波 VSWR			1.35	:1
阻抗 Impedance		50		Ohms
射频功率值 RF Power Rating	25 Watts Average at 25°C			

### 环境和机械特性 Environmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
壳体材质 Body Material	Black, finned aluminum	
连接器材质 Connector Material	Nickel plated brass	
内导体 Inner Conductor	Gold-plated phosphor bronze	
接口 Connectors	N Female/Male	

外形图 Outline Drawing: Unit:mm



订货信息 Ordering Information:

标准型号 Base Number	描述 Description
TA03A25-N-12.4	Coaxial Fixed Attenuator, DC-12.4GHz, 3±0.8dB Attenuation
TA06A25-N-12.4	Coaxial Fixed Attenuator, DC-12.4GHz, 6±0.8dB Attenuation
TA10A25-N-12.4	Coaxial Fixed Attenuator, DC-12.4GHz, 10±0.8dB Attenuation
TA20A25-N-12.4	Coaxial Fixed Attenuator, DC-12.4GHz, 20±0.8dB Attenuation
TA30A25-N-12.4	Coaxial Fixed Attenuator, DC-12.4GHz, 30±1.0dB Attenuation
TA40A25-N-12.4	Coaxial Fixed Attenuator, DC-12.4GHz, 40±1.0dB Attenuation