

## Power Limiter

DC-40GHz /2W,Power Handling

Model: TLMTDC40G-33-16

The TLMTDC40G-33-16 is a broadband limiter product. This limiter has an operating frequency range that can cover DC-40 GHz and features stable performance.

### Features:

- Ultra Wide Band:DC-40 GHz
- RF Power Handling:2W(CW)
- Limiting power:16 dBm
- Low Insertion Loss
- 50 Ohm Matched Input / Output

### Applications:

- Communication receiver
- Laboratory test
- Sensor radar

### 电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	DC-40			GHz
插损 Insertion Loss		1.3		dB
限幅电平 Limiting power		16		dBm
输入回波损耗 Input Return Loss		-12		dB
输出回波损耗 Output Return Loss		-12		dB
耐功率 Power handling(cw)			33	dBm
阻抗 Impedance	50			Ohms



### 机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Male/2.92mm Female	
长度 Length	42.2	mm

## 绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	+33 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

## 外形图 Outline Drawing: Unit:mm



## 温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

## 订货信息 Ordering Information:

## 典型曲线 Typical Performance Data:

