

Power Amplifier

0.5-6GHz/43dB Gain/40 dBm Psat

Model: TLPA0.5G6G-40-40

TLPA0.5G6G-40-40 is a power amplifier with a typical small signal gain of 43 dB and a nominal Psat of 40 dBm across the frequency range of 0.5 to 6 GHz. The DC power requirement for the amplifier is +28 VDC/2 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 0.5-6GHz
- Gain: 43dB Typ
- Output Power Psat: 40dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range		0.5-6		GHz
小信号增益 Small Signal Gain	40	43		dB
增益平坦度 Gain Flatness		±2.5	±3.5	dB
线性输出功率 Output P1dB	37	38		dBm
饱和输出功率 Output Psat	40			dBm
杂散 Spurious		-60		dBc
谐波抑制 Harmonic		-15	-13	dBc
输入驻波 Input VSWR		1.5	2.5	:1
直流电压 DC Voltage		28	29	V DC
直流电流 DC Supply Current		2		A
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	125*95*18(Without Heatsink) 160*162*68(With Heatsink)	mm
重量 Weight	2	Kg

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+29 V
输入功率 RF Input Power	+8 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+40	°C
存储温度 Non-operating Temperature*	-30		+50	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA0.5G6G-40-40	Power amplifier 0.5-6GHz,Gain:43dB,Psat:40dBm, +28V DC,Without Heatsink	Rev.1.1
TLPA0.5G6G-40-40-HS	Power amplifier 0.5-6GHz,Gain:43dB,Psat:40dBm, +28V DC,With Heatsink	Rev.1.1


典型曲线 Typical Performance Data:

Input VSWR&Gain vs Frequency


Input VSWR&Gain(dB)

典型曲线 Typical Performance Data:

Gain vs Output Power



P1dB vs Frequency



P3dB vs Frequency

P3dB (dBm)