

Power Amplifier

12-18GHz/47dB Gain/40dBm Psat

Model: TLPA12G18G-47-40

TLPA12G18G-47-40 is a power amplifier with a minimum power gain of 47 dB and a minimum Psat of 40 dBm across the frequency range of 12 to 18 GHz. The DC power requirement for the amplifier is +28 VDC/3 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 12-18GHz
- Gain: 47dB Min
- Output Power Psat: 40dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	12-18			GHz
功率增益 Power Gain	47			dB
增益平坦度 Gain Flatness		±2		dB
线性输出功率 Output P1dB		37		dBm
饱和输出功率 Output Psat	40			dBm
输入驻波 Input VSWR		2		:1
直流电压 DC Voltage		28		V DC
直流电流 DC Supply Current		3		A
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:




参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Feedthru capacitors	
尺寸 Size	60*60*11(Without heatsink) 188*125*146(With heatsink)	mm
重量 Weight	≤200	g

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+29 V
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+50	°C
存储温度 Non-operating Temperature*	-50		+60	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA12G18G-47-40	Power amplifier 12-18GHz, Gain:47dB,Psat:40dBm,+28V DC,Without Heatsink	Rev.1.1
TLPA12G18G-47-40-HS	Power amplifier 12-18GHz, Gain:47dB,Psat:40dBm,+28V DC,With Heatsink	Rev.1.1


典型曲线 Typical Performance Data:

Input VSWR vs Frequency


Input VSWR

典型曲线 Typical Performance Data:

Small Signal Gain vs Frequency



PndB vs Frequency




Pout@Pin




典型曲线 Typical Performance Data:

Pout@Equal_Pin



Spurious vs Frequency



Harmonic vs Frequency

Harmonic (dBc)