

## Power Amplifier 15-44GHz/25dB Gain/20dBm P1dB

Model: TLPA15G44G-25-20

TLPA15G44G-25-20 is a power amplifier with a typical small signal gain of 25 dB and a minimum P1dB of 20 dBm across the frequency range of 15 to 44 GHz. The DC power requirement for the amplifier is +12 VDC/214 mA. The input and output port configuration offers coax adapter structure with 2.4mm female.

### Features:

- Frequency range: 15-44GHz
- Gain: 25dB Typ
- Output Power P1dB: 20dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

### Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

## 电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range		15-44		GHz
小信号增益 Small Signal Gain		25		dB
增益平坦度 Gain Flatness		±2.5		dB
线性输出功率 Output P1dB		20		dBm
输入驻波 Input VSWR			2.5	:1
输出驻波 Output VSWR			2.5	:1
直流电压 DC Voltage	10	12	13	V DC
直流电流 DC Supply Current		210		mA
阻抗 Impedance		50		Ohms


## 机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.4mm Female/2.4mm Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	44*36*12	mm

## 绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15 V
输入功率 RF Input Power	+20 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

## 外形图 Outline Drawing: Unit:mm



**\*\*\*Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

## 温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

\*Note: For a wider temperature range, please consult the manufacturer.

## 订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA15G44G-25-20	Power amplifier 15-44GHz, Gain:25dB,P1dB:20dBm,+12V DC,Without Heatsink	Rev.1.1
TLPA15G44G-25-20-HS	Power amplifier 15-44GHz, Gain:25dB,P1dB:20dBm,+12V DC,With Heatsink	Rev.1.1


## 典型曲线 Typical Performance Data:

### VSWR&Gain vs Frequency


VSWR&Gain

## 典型曲线 Typical Performance Data:

### Gain vs Output Power



### P1dB vs Frequency



### P3dB vs Frequency

