

18-40GHz, Gain:35dB, Psat:33dBm

Feature:

- Ultra Wide Band: 18-40GHz
- Gain:35dB Min
- Psat Output Power:33dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

电气特性 Electrical Specifications:

参数Parameter	Min	Typ	Max	单位Units
频率范围 Frequency range	18-40			GHz
增益 Gain	35			dB
线性输出功率平坦度 Output P1dB Flatness			±2	dB
线性输出功率 Output P1dB	30			dBm
饱和输出功率 Output Psat		33		dBm
输入驻波 Input VSWR		2		:1
杂散 Spurious@Pout=30dBm			-50	dBc
直流电压 DC Voltage		+24		V DC
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:

参数Parameter	指标 Value	单位Units
输入输出接口 Input /Output Connector	2.92 Female/2.92 Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	150*90*20	mm
重量 Weight	500	g


绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	1-5:+24V 6-9:GND
输入功率 RF Input Power	0dBm



Available 220V System

Unit: mm



***Heat Sink Required During Operation

J30J-9ZKP引脚定义	
Pin	Function
1-5	+24V
6-9	GND



温度环境 Environmental Conditions:

参数Parameter	Min	Typ	Max	单位Units
操作温度 Operating Temperature	-25		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity	100%RH at 35°C, 95%RH at 40°C			%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
------------------	----------------	-------------