

## 2.7GHz-3.5GHz, Gain:25dB, Psat:56dBm

### Feature:

- Wide Band: 2.7GHz-3.5GHz
- Gain: 25dB Typ
- Psat Output Power: 56 dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

### 电气特性 Electrical Specifications:

参数Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	2.7-3.5			GHz
功率增益 Power Gain	20	25		dB
增益平坦度 Gain Flatness		±1	±2	dB
线性输出功率 Output P1dB		50		dBm
饱和输出功率 Output Psat	56	57		dBm
谐波抑制 Harmonics @Pout=56dBm			20	dBc
输入驻波 Input VSWR		1.5	2.0	:1
直流电压 DC Voltage	26	28	30	V DC
直流电流 DC Supply Current		50	70	A
阻抗 Impedance	50			Ohms

### 机械特性 Mechanical Specifications:


参数Parameter	指标 Value	单位Units
输入/输出接口 Input /Output Connector	SMA/N Female	
直流偏置 DC Bias	Four core avionics	
尺寸 Size	366*358*141	mm
重量 Weight	14	Kg

### 绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	30V
输入功率 RF Input Power	40 dBm



Unit: mm



### \*\*\*Heat Sink Required During Operation



#### 温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+50	°C
存储温度 Non-operating Temperature*	-30		+60	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	20g,11ms,saw-tooth			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


\*Note: For a wider temperature range, please consult the manufacturer.

#### 订货信息 Ordering Information:


标准型号 Part Number	描述 Description	版本号Revision
------------------	----------------	-------------

Test TEM=25°C:


## Input VSWR vs Frequency



## Small Signal Gain vs Frequency




## Gain vs Output Power




Test TEM=25°C:


### P1dB&P3dB&P5dB vs Frequency



### Psat vs Frequency




### 2nd Harmonics vs Output Power




Test TEM=25°C:

### 3rd Harmonics vs Output Power




### 4th Harmonics vs Output Power




Test TEM=-20°C:

### Input VSWR vs Frequency




Test TEM=-20°C:


## Small Signal Gain vs Frequency



## Gain vs Output Power




## P1dB&P3dB&P5dB vs Frequency




Test TEM=-20°C:


### Psat vs Frequency



### 2nd Harmonics vs Output Power




### 3rd Harmonics vs Output Power




Test TEM=-20°C:

### 4th Harmonics vs Output Power




Test TEM=50°C:

### Input VSWR vs Frequency




### Small Signal Gain vs Frequency




Test TEM=50°C:


### Gain vs Output Power



### P1dB&P3dB&P5dB vs Frequency




### Psat vs Frequency




Test TEM=50°C:

### 2nd Harmonics vs Output Power



### 3rd Harmonics vs Output Power



### 4th Harmonics vs Output Power

