

0.06-0.3GHz, Gain:30dB, P1dB:36dBm

Feature:

- Ultra Wide Band: 0.06-0.3GHz
- Gain:30dB Min
- P1dB Output Power:36dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

电气特性 Electrical Specifications:

参数Parameter	Min	Typ	Max	单位Units
频率范围 Frequency range	0.06-0.3			GHz
增益 Gain	30			dB
增益平坦度 Gain Flatness		±1	±2	dB
线性输出功率 Output P1dB	36			dBm
饱和输出功率 Output Psat	37			dBm
输入驻波 Input VSWR			2	:1
直流电压 DC Voltage		+28		V DC
直流电流 DC Supply Current		0.5		A
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:

参数Parameter	指标 Value	单位Units
输入输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	130*140*23	mm
重量 Weight	/	g

绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+28V
输入功率 RF Input Power	12dBm



Available 220V System

Unit: mm



*****Heat Sink Required During Operation**



温度环境 Environmental Conditions:

参数Parameter	Min	Typ	Max	单位Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	30,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TLPA60M0.3G-30-36	Power amplifier 0.06-0.3GHz,Gain:30dB,P1dB:36dBm,+28V DC,Without Heatsink.	Rev.1.0