

6-18GHz, Gain:35dB, Psat:33dBm

Feature:

- Ultra Wide Band: 6-18GHz
- Gain:35dB Min
- Psat Output Power:33dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

电气特性 Electrical Specifications:

参数Parameter	Min	Typ	Max	单位Units
频率范围 Frequency range	6-18			GHz
增益 Gain	35			dB
饱和输出功率 Output Psat	33			dBm
杂散 Spurious			-50	dBc
谐波 Harmonics			-10	dBc
输入驻波 Input VSWR			2	:1
直流电压 DC Voltage		+28		V DC
直流电流 DC Supply Current	1.1			A
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:

参数Parameter	指标 Value	单位Units
输入输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	59.1*35.4*7.9	mm
重量 Weight	/	g

绝对最大值 Absolute Maximum Ratings:


参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	TBD



Available 220V System

Unit: mm

J30J-9ZKP	
1-4	+28V
5-9	GND



***Heat Sink Required During Operation




温度环境 Environmental Conditions:

参数Parameter	Min	Typ	Max	单位Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	30,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
------------------	----------------	-------------

Input VSWR vs Frequency




Gain vs Frequency




Pout@Equal_Pin

Pout(dBm)

P1dB vs Frequency



Spurious@Pout=33dBm



Harmonics@Pout=33dBm

Harmonics(dBc)

Pout@Pin

