

Power Amplifier

8-12GHz /30dB Gain/33 dBm Psat

Model: TLPA8G12G-30-33

TLPA8G12G-30-33 is a power amplifier with a power gain of 30 dB and a nominal Psat of 33 dBm across the frequency range of 8 to 12 GHz. The DC power requirement for the amplifier is +12 VDC/0.6 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Ultra Wide Band: 8-12 GHz
- Gain: 30dB Min
- Output Power Psat: 33dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	8-12			GHz
功率增益 Power Gain	30			dB
增益平坦度 Gain Flatness			±2	dB
线性输出功率 Output P1dB	30			dBm
饱和输出功率 Output Psat		33		dBm
杂散 Spurious		-60		dBc
输入驻波 Input VSWR		2	2.2	:1
输出驻波 Output VSWR		2	2.5	:1
直流电压 DC Voltage		12		V DC
直流电流 DC Supply Current			600	mA
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	58.5*38*12.5	mm
重量 Weight	/	g

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+20 V
输入功率 RF Input Power	+15 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA8G12G-30-33	Power amplifier 8-12GHz,Gain:30dB,Psat:33dBm, +12V DC,Without Heatsink	Rev.1.1
TLPA8G12G-30-33-HS	Power amplifier 8-12GHz,Gain:30dB,Psat:33dBm, +12V DC,With Heatsink	Rev.1.1