



B Electrical & Environmental Characteristics	
Impedance	50Ω
Insulation Resistance	≥5000MΩ
Operating Frequency	DC~40GHz
Dielectric Withstanding Voltage	325V
VSWR	≤1.25
Hermeticity	≤1.1013x10 <sup>-3</sup> Pa · cm <sup>3</sup> /sHe
Operating Temperature	- 55~+165°C
Material & Coat-Plating	
A Inner Conductor	4J29
Dielectric	Glass

No.	Model	X
1	TLSPMC01	有限擒纵
2	TLSPMC01F	全擒纵

  

THIS DRAWING IS A CONTROLLED DOCUMENT	DWN	Turpanic Co, Ltd ,Inc			
	CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	Product Model  <b>TLSPMC01</b> SSMP male, HERMETIC SEALED Adaptor			
	0 PLC ±0.25		PRODUCT SPEC		
	1 PLC ±0.15				
	2 PLC ±0.12				
3 PLC ±	APPLICATION SPEC				
3 PLC ±					
ANGLES ±1°					
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO