

## 75-110GHz, NF:5.0 dB, Gain:35 dB

### Feature:

- Ultra Wide Band: 75-110 GHz
- Gain:35dB Typ
- Noise Figure:5.0dB Typ
- Unconditional stability

### 电气特性 Electrical Specifications:

参数Parameter	Min	Typ	Max	单位Units
频率范围 Frequency range	75		110	GHz
增益 Gain		35		dB
增益平坦度 Gain Flatness		±2		dB
噪声系数 Noise Figure		5.0		dB
输出功率1dB压缩点 Output P1dB		8		dBm
输入驻波 Input VSWR		2		:1
直流电压 DC Voltage		+12		V DC
直流供电 DC power supply		50		mA

### 机械特性 Mechanical Specifications:

参数Parameter	指标 Value	单位Units
输入接口 Input Connector	WR-10/ UG-387/U	
输出接口 Output Connector	WR-10/ UG-387/U	
供电引脚 Power Supply Pin	Solder Pin	
尺寸 Size	38.1*27.94*19.05	mm


### 绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15 V
输入功率 RF Input Power	0dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



Available 220V System  
Benchtop Amplifier

Unit: mm




## 温度环境 Environmental Conditions:

参数Parameter	Min	Typ	Max	单位Units
操作温度 Operating Temperature	0		+65	°C
存储温度 Non-operating Temperature	-45		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


## 订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TMLA-075110-3550-10-E	Low Noise Amplifier,75-110GHz, Noise Figure:5.0dB, Gain:35dB,+12V DC,WR-10	Rev.1.1

### Gain vs Frequency



### Noise Figure vs Frequency



### VSWR vs Frequency

